



| ROUND BELTS | | | | | | | | | | |
|-----------------|-----------|-----------|-----------|-----------|-----------|-----------|---------|--------|---------|--------|
| SECTION / COLOR | | | | | | | | | | |
| DESCRIPTION | RSGR 88 | RSRGR 88 | RSO 90 | RSRO 90 | RTRS 85 | | | | | |
| HARDNESS (ShrA) | 88 | 88 | 90 | 90 | 85 | | | | | |
| TEMP. RANGE | -30 / +60 | -30 / +60 | -30 / +70 | -30 / +70 | -40 / +55 | | | | | |
| C.OF FRICTION | 0,38 | 0,40 | 0,45 | 0,50 | 0,55 | | | | | |
| DIAMETER (mm) | MPD(mm) | PF(%1) | MPD(mm) | PF(%1) | MPD(mm) | PF(%1) | MPD(mm) | PF(%1) | MPD(mm) | PF(%1) |
| 2 | 18 | 0,12 | - | - | RSO 90 | RSO 90 | - | - | - | - |
| 3 | 30 | 0,32 | - | - | 90 | 90 | - | - | - | - |
| 4 | 37 | 0,53 | - | - | -30 / +70 | -30 / +70 | - | - | - | - |
| 5 | 49 | 0,86 | - | - | 0,45 | 0,45 | - | - | 40 | 0,50 |
| 6 | 58 | 1,21 | 60 | 16,00 | RSO 90 | RSO 90 | 60 | 16,00 | 48 | 0,60 |
| 7 | 67 | 1,67 | - | - | 90 | 90 | - | - | - | - |
| 8 | 75 | 2,16 | 78 | 19,00 | -30 / +70 | -30 / +70 | 80 | 19,00 | 64 | 0,90 |
| 9 | 87 | 2,77 | - | - | 0,45 | 0,45 | - | - | - | - |
| 10 | 95 | 3,40 | 101 | 22,00 | RSO 90 | RSO 90 | 101 | 22,00 | 80 | 1,21 |
| 12 | 113 | 4,88 | 119 | 25,00 | 90 | 90 | 119 | 25,00 | 96 | 1,70 |
| 15 | 142 | 7,64 | 152 | 28,00 | -30 / +70 | -30 / +70 | 152 | 28,00 | - | - |
| 18 | 174 | 11,30 | 178 | 36,00 | 0,45 | 0,45 | 178 | 36,00 | - | - |
| 20 | 188 | 13,56 | - | - | RSO 90 | RSO 90 | - | - | - | - |

| DOUBLE V BELTS | | | | |
|-----------------|----------|-----------|---------|--------|
| SECTION / COLOR | | | | |
| DESCRIPTION | DVS 85 | DVS 92 | | |
| HARDNESS (ShrA) | 85 | 92 | | |
| TEMP. RANGE | -30 / 60 | -30 / +60 | | |
| C. OF FRICTION | 0,55 | 0,45 | | |
| SIZE (mm) | MPD(mm) | PF(%1) | MDF(mm) | PF(%1) |
| 24 x 9,5 x 6,8 | 45 | 2,00 | 60 | 10,00 |
| 21 x 8,5 x 8,5 | 40 | 1,70 | 56 | 8,00 |
| 15 x 5,5 x 8,5 | 25 | 1,00 | 31 | 6,00 |

| V - BELTS | | | | | | | | |
|-----------------|-----------|-----------|-----------|-----------|---------|--------|---------|--------|
| SECTION / COLOR | | | | | | | | |
| DESCRIPTION | VSW 85 | VSWR 85 | VSB 88 | VSBR 88 | | | | |
| HARDNESS (ShrA) | 85 | 85 | 88 | 88 | | | | |
| TEMP. RANGE | -30 / +60 | -30 / +60 | -30 / +70 | -30 / +70 | | | | |
| C.OF FRICTION | 0,55 | 0,55 | 0,45 | 0,45 | | | | |
| SIZE (mm) | MPD(mm) | PF(%1) | MPD(mm) | PF(%0,5) | MPD(mm) | PF(%1) | MPD(mm) | PF(%1) |
| M = 8 x 5,2 | 39 | 0,70 | - | - | 60 | 3,00 | - | - |
| Z = 10 x 6,5 | 45 | 1,00 | - | - | 65 | 4,10 | - | - |
| A = 13 x 8 | 50 | 1,60 | 50 | 12,00 | 80 | 6,70 | 80 | 6,70 |
| B = 17 x 11,5 | 75 | 2,90 | 75 | 18,00 | 115 | 12,10 | 115 | 12,10 |
| C = 22 x 14,5 | 100 | 4,80 | 100 | 22,00 | 145 | 20,00 | 145 | 20,00 |
| D = 32 x 21,5 | 145 | 10,40 | 145 | 24,00 | 215 | 43,00 | 215 | 43,00 |

| DIAMOND TOP V - BELTS | | | | | | | | |
|-----------------------|-----------|------------|-----------|------------|---------|--------|---------|--------|
| SECTION / COLOR | | | | | | | | |
| DESCRIPTION | VSW 85 DT | VSWR 85 DT | VSB 88 DT | VSBR 88 DT | | | | |
| HARDNESS (ShrA) | 85 | 85 | 88 | 88 | | | | |
| TEMP. RANGE | -30 / +60 | -30 / +60 | -30 / +70 | -30 / +70 | | | | |
| C.OF FRICTION | 0,55 | 0,55 | 0,45 | 0,45 | | | | |
| SIZE (mm) | MPD(mm) | PF(%1) | MPD(mm) | PF(%0,5) | MPD(mm) | PF(%1) | MPD(mm) | PF(%1) |
| A = 13 x 16 | 110 | 2,70 | 110 | 16,00 | 150 | 5,60 | 150 | 5,60 |
| B = 17 x 19,5 | 130 | 4,30 | 130 | 19,00 | 185 | 9,30 | 185 | 9,30 |
| C = 22 x 24,5 | 165 | 7,90 | 165 | 38,00 | 235 | 14,30 | 235 | 14,30 |

| SUPERGRIP V - BELTS | | | | | | | | | | |
|---------------------|--------------------------------------|---------------------------------------|---------------------------------|----------------------------------|--------------------------------------|---------------------------------------|---------|----------|---------|--------|
| SECTION / COLOR | | | | | | | | | | |
| DESCRIPTION | VSW 85 GT Polyurethane GT Coating | VSWR 85 GT Polyurethane GT Coating | VSW 85 GGT Rubber GT Coating | VSWR 85 GGT Rubber GT Coating | VSB 88 GT Polyurethane GT Coating | VSBR 88 GT Polyurethane GT Coating | | | | |
| HARDNESS (ShrA) | 85 | 85 | 85 | 85 | 88 | 88 | | | | |
| TEMP. RANGE | -30 / +60 | -30 / +60 | -30 / +60 | -30 / +60 | -30 / +70 | -30 / +70 | | | | |
| C.OF FRICTION | 0,55 | 0,55 | 0,55 | 0,55 | 0,45 | 0,45 | | | | |
| SIZE (mm) | MPD(mm) | PF(%1) | MPD(mm) | PF(%0,5) | MPD(mm) | PF(%1) | MPD(mm) | PF(%0,5) | MPD(mm) | PF(%1) |
| A = 13 x 16 | 50 | 1,60 | 50 | 12,00 | 50 | 1,60 | 50 | 12,00 | 80 | 6,70 |
| B = 17 x 19,5 | 75 | 2,90 | 75 | 18,00 | 75 | 2,90 | 75 | 18,00 | 115 | 12,10 |
| C = 22 x 24,5 | 100 | 4,80 | 100 | 22,00 | 100 | 4,80 | 100 | 22,00 | 145 | 20,00 |

| V - BELTS | | | | |
|-----------------|---|---|---------|--------|
| SECTION / COLOR | | | | |
| DESCRIPTION | VSWR 85 FG Polyurethane Flat Coating | VSWR 88 FG Polyurethane Flat Coating | | |
| HARDNESS (ShrA) | 85 | 88 | | |
| TEMP. RANGE | -30 / 60 | -30 / +70 | | |
| C.OF FRICTION | 0,55 | 0,45 | | |
| SIZE (mm) | MPD(mm) | PF(%0,5) | MPD(mm) | PF(%1) |
| A = 13 x 16 | 50 | 12,00 | 80 | 6,70 |
| B = 17 x 19,5 | 75 | 18,00 | 115 | 12,10 |
| C = 22 x 24,5 | 100 | 22,00 | 145 | 20,00 |

MPD : Minimum Pulley Diameter PF : Pull Force (%) in Kg

ATK BANT VE KAYIŞÇILIK SAN. TİC. LTD .ŞTİ.